



NOTE:
Rating: DC 30V 0.1A
Operating Force: 30±10gf
Lifetime: 50,000 Cycles

| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|----------------|---------|------|-----------------|-----------|--------|
| ⑥ | Contact Spring | — | 1 | Phosphor Bronze | Ag Plated | — |
| ⑤ | Base | — | 1 | PA46 | Black | — |
| ④ | Terminal | — | 2 | Phosphor Bronze | Ag Plated | — |
| ③ | Trestle | — | 1 | SPCC | Ni Plated | — |
| ② | Cover | — | 1 | PA46 | Black | — |
| ① | Knob | — | 1 | PA46 | Black | — |

| APPROVALS | | DATE |
|-----------|-----------|----------|
| DRAWN | J.X.Zhang | 2013/9/9 |
| CHECKED | | |

| APPROVALS | | TITLE: | PART NO. | SCALE: | PROJ. |
|----------------|-------|------------------|--------------|--------|-------|
| APPROVALS | | DETECTOR SWITCHS | K5-1659SA-02 | 1:1 | ① |
| TOLERANCES ARE | | ANGLE | UNIT: | SCALE: | PROJ. |
| 30~12.5 | ±0.30 | ±2' | mm | 1:1 | ① |
| 10~30 | ±0.20 | | | | |
| 5~10 | ±0.15 | | | | |
| ~5 | ±0.10 | | | | |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|--------------|---------|--------|--------|
| | A | | NEW | | | |

OKHRO
ELECTRONICS CO.,LTD