



NOTE:
 Rating: DC 30V 0.1A
 Operating Force: 50±10gf
 Lifetime: 100,000 Cycles
 Packaging: 1000pcs/kg

| | | | | | | |
|------|----------------|---------|------|-----------------|-----------|--------|
| ⑤ | Contact Spring | — | 1 | Phosphor Bronze | Ag Plated | — |
| ④ | Terminal | — | 2 | Phosphor Bronze | Ag Plated | — |
| ③ | Base | — | 1 | PA46 | Black | — |
| ② | Cover | — | 1 | PA46 | Black | — |
| ① | Slider | — | 1 | PA46 | Black | — |
| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |

| | | | | | | |
|----------------|------|-----------|--------------|------------------|--------|--------|
| DRAWN | | DATE | | TITLE | | |
| JIANKUN.LIU | | 2015.5.13 | | DETECTOR SWITCHS | | |
| CHECKED | | APPROVALS | | PART NO. | | |
| APPROVALS | | APPROVALS | | K5-1610DA-01 | | |
| TOLERANCES ARE | | ANGLE | | SCALE: 1:1 | | |
| 30°~45° ±0.30 | | ±2° | | PROJ: ① | | |
| 10°~30 ±0.20 | | ±2° | | SHEET 1 OF 1 | | |
| 5°~10 ±0.15 | | ±2° | | | | |
| ~5 ±0.10 | | ±2° | | | | |
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | A | | NEW | | | |