



### SPECIFICATIONS:

- Voltage Rating: 250V AC Min
- Current Rating: 2.0A Min
- Dielectric Strength: 1000V AC For 1 Minute
- Insulation Resistance: 1000Mmegohms Min
- Contact Resistance: 30Milliohms Max
- Operation Temperature: -55°C To +125°C
- Product Withstanding Reflow Soldering: 260°C For 15s
- Durability :5000 Cycles
- Normal Force At Working Position: 80g Min
- Insertion Force:>3N
- Insulator: High Temperature Thermoplastic
- UL 94V-0 Black (LCP Black)
- Contact: Beryllium Copper,  
Gold Flash Over Nickel

②	Terminal	—	3	Phosphor Bronze	Au Plated	—
①	Housing	—	1	LCP	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
APPROVALS		DATE				
DRAWN	xu qi feng	2014.12.05				
CHECKED		TITLE:	ELECTRONICS CO.,LTD			
APPROVALS		PART NO.	BC-10-3PD			
TOLERANCES ARE		UNIT:	SCALE:	PROJ:		
30~12.5	±0.30	mm	1:1	SHEET 1 OF 1		
10~30	±0.25					
5~10	±0.20					
~5	±0.15					

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			